

KBF 240 (E5.2) - Constant climate chamber

The KBF series was particularly designed for absolutely reliable stability tests and precise maintenance of constant climatic conditions. With its large reserve capacity and many optional features, it is designed to meet future challenges for many years to come.



2



► Performance features and equipment:

- Electronically controlled APT.line™ preheating chamber and refrigerating system assuring temperature accuracy and reproducible results
- Temperature range 0 °C (32 °F) up to 70 °C (158 °F) - without humidity
- Humidity range 10 % RH to 80 % RH
- MCS controller with 25 storable programs of 100 sections each for a maximum of 500 program segments
- Features:
 - User friendly LCD screen
 - Easy-to-read menu guide
 - Integrated electronic chart recorder
 - Variety of options for the graphic display of process parameters
 - Real time clock
- Electronically controlled humidification and dehumidification system with capacitive humidity sensor
- Suitable for stability tests according to ICH guideline Q1A
- Inner glass door with sealing
- Independent adjustable temperature safety device class 3.1 (DIN 12880), with visual and audible temperature alarm
- Access port with silicone plug Ø 30 mm (1.18 inch), left side
- Safety connection kit for water supply and drainage, including water hose, total length 6 m (19.7 ft.)
- Ethernet interface for GLP/GMP and the FDA guideline 21 CFR Part 11 compliant APT-COM™ DataControlSystem software
- 2 stainless steel racks included
- BINDER test certificate



KBF 240 (E5.2)

Temperature-humidity chart

Exterior dimensions	
Width (mm/inch)	925 / 36.4
Height (inclusive feet/casters) (mm/inch)	1460 / 57.5
Depth (mm/inch)	800 / 31.5
Plus door handle, I-panel, connection (mm/inch)	50 / 2.0
Wall clearance rear (mm/inch)	100 / 3.9
Wall clearance side (mm/inch)	100 / 3.9
Steam space volume (l/cu.ft.)	348 / 12.3
Number of doors	1
Number of inner glass doors	1


Interior dimensions	
Width (mm/inch)	650 / 25.6
Height (mm/inch)	785 / 30.9
Depth (mm/inch)	470 / 18.5
Interior volume (l/cu.ft.)	247 / 8.7
Racks (number standard/max.)	2 / 9
Load per rack (kg/lbs.)	30 / 66
Permitted total load (kg/lbs.)	100 / 221
Weight of the unit (empty) (kg/lbs.)	184 / 406

Temperature data (without humidity)	
Temperature range (°C/°F)	0 - 70 / 32 - 158
Temperature variation	
at 25 °C (77 °F) (±K)	0.2
at 40 °C (104 °F) (±K)	0.3
Temperature fluctuation (± K)	0.1
Max. heat compensation up to 40 °C (104 °F) (W)	300

Climatic data (with humidity)	
Temperature range (°C/°F)	10 - 70 / 50 - 158
Temperature variation	
at 25 °C (77 °F) / 60 % RF (±K)	0.3
at 40 °C (104 °F) / 75 % RF (±K)	0.3
Temperature fluctuation	
at 25 °C (77 °F) / 60 % RF (±K)	0.1
at 40 °C (104 °F) / 75 % RF (±K)	0.1
Humidity range (% RH)	10 - 80

A: Standard Climate range / B: Discontinuous range

Heat compensation



Humidity fluctuation (\pm % RH)	
at 25 °C (77 °F) / 60% RF	1.5
at 40 °C (104 °F) / 75% RF	1.5
Recovery time after doors were open for 30 sec. 2)	
at 25 °C (77°F) / 60% RH) (Min.)	4
at 40 °C (104 °F) / 75% RH) (Min.)	5
Electrical data	
Nominal voltage (\pm 10%) 50 / 60 Hz (V)	200 - 240
Nominal power (kW)	2.1
Energy consumption at 40 °C (104 °F) / 75 % RF (W)3)	650
Noise level (dB (A))	52

2. We recommend the BINDER Pure Aqua Service for longer maintenance intervals, regardless of water quality.

2




3. Demineralized or deionized water available at the customers location.

1) Data valid at an ambient temperature of 25 °C (77 °F)

2) up to 98 % of the set value

3) These values can be used upon calculation of air conditioning systems

All technical data are specified for units with standard equipment at an ambient temperature of 20 °C (68 °F) and a voltage fluctuation of \pm 10 %. The temperature data are determined in accordance to factory standard following DIN 12880 respecting the recommended wall clearances of 10 % of the height, width and depth of the inner chamber. All indications are average values, typical for units produced in series. We reserve the right to alter technical specifications at all times.



▶ Access ports

With silicon plugs for inserting external measuring devices into the chamber. Access ports with 10, 50, and 100 mm diameter.



▶ BINDER Pure Aqua Service

Our efficient, flexible water purification system delivers top water quality and extends the maintenance period. Special feature: Our system uses a disposable purification cartridge and also has a water quality indicator.



▶ External fresh water supply set

External fresh water supply set consists of fresh and waste water canister, cabling and pump.



▶ Specimen temperature measurement

Additional flexible PT 100 temperature sensor for precise temperature measurement of the specimen with digital temperature display. Recording of measured data possible via Ethernet or RS 422 interface.

**KBF 240 (E5.2)**

Securing elements for additional fastening of racks (1 set of 4).	<input type="radio"/>
Access port with silicone plugs, 30 mm (1.18 inch), 50 mm (1.97 inch), 100 mm (3.94 inch)	<input type="radio"/>
Additional PT 100 temperature sensor, flexibly installed, with external connection, including LEMO connector (3 - pin)	<input type="radio"/>
RS 422 connection for communication software APT - COM™ DataControlSystem	<input type="radio"/>
External fresh supply set consists of fresh and waste water canister, cabling and pump	<input type="radio"/>
BINDER PURE AQUA SERVICE consisting of disposable cartridge, hose set and measuring unit	<input type="radio"/>
Factory calibration certificate for temperature and humidity. Measurement in center of chamber at 25 °C (77 °F) / 60% RH or at specified values	<input type="radio"/>
Extension to factory calibration certificate for temperature and humidity. Each additional measurement at an additional measuring point or set of values	<input type="radio"/>
Temperature precision measurement according to DIN 12880 and 9 - point humidity measurement / factory standard with measurement log and certificate, measured at 25 °C (77 °F) / 60% RH or at specified values	<input type="radio"/>
Rack, stainless steel	<input type="radio"/>
Reinforced rack, stainless steel, with 1 set of securing elements (4 pieces) (max. load 70 kg / 154 lbs.)	<input type="radio"/>
Shelf, perforated, stainless steel	<input type="radio"/>
Safety device, Class 3.3 (DIN 12880) with optical alarm	<input type="radio"/>
4 - 20 mA analog output for temperature and humidity measurements (e.g. chart recorder connection), with 6 - pin DIN socket. Outputs are adjusted automatically as the controller is adjusted	<input type="radio"/>
Zero - voltage relay alarm outputs for temperature (± 2 °C) and humidity (± 5 % RH), accessible via 6 - pin DIN socket, with acoustic signal that can be switched off (maximum power rating 24 V AC / DC, 2.5 A)	<input type="radio"/>
Switchable waterproof interior socket 230 V AC (max. 500 W), IP 65 protected, with corresponding plug (IP 66 protected)	<input type="radio"/>
Lockable door	<input type="radio"/>